

APB ProSpec & ProRack Interconnect Guide						
			ProSpec-1U	ProSpec-2U	ProRack	
Signal	Signal Type	Level	DB-9F Pin #	DB-15F Pin #	Din-5 Pin #	Notes
Left-Mix	Internal Audio Mix Bus	-2dBu	1	1		Connect these points together to combine buses across Mixers
Center/Mono-Mix	Internal Audio Mix Bus	-2dBu	2	2		Connect these points together to combine buses across Mixers
Right-Mix	Internal Audio Mix Bus	-2dBu	6	9		Connect these points together to combine buses across Mixers
Aux-Mix	Internal Audio Mix Bus	-2dBu	X	10		Connect these points together to combine buses across Mixers
HPHONE-L Out	Ext Audio Feed Out	Varies	9	12		Connect to ProRack Solo-In L
HPHONE-R Out	Ext Audio Feed Out	Varies	5	5		Connect to ProRack Solo-In R
Solo Tally	Logic Signal	Floats, 0V when Solo Active	8	11		DGND shows Solo Active
Solo DC	Logic Signal	+6V, 0V to Activate	3	4	5	Connect to DGND to activate Solo
DGND	Logic Ground	0V Logic Ref	4	7	3	Digital Gnd Ref Bus
AGND	Audio Ground	0V Audio Ref	7	3	2	Audio Gnd Ref Bus
Solo-In L	Ext Audio Feed In	-2dBu	X	X	1	Feed from ProSpec HPHONE-L Out
Solo-In R	Ext Audio Feed In	-2dBu	X	X	4	Feed from ProSpec HPHONE-R Out